



AEGIS AE20070-60.43
Specifications

Case dimensions

Internal Dimensions	1900	x	600	x	952	mm
External Dimensions	2000	x	700	x	1029	mm
Internal Volume	1.085	m ³				
Buoyancy In Water	1085	Kg				

Base dimensions

Internal Dimensions	1900	x	600	x	590	mm
External Dimensions	2000	x	700	x	600	mm

Lid dimensions

Internal Dimensions	1900	x	600	x	362	mm
External Dimensions	2000	x	700	x	429	mm

Case Material	Rotomoulded Polyethylene (LLDPE)
Latch Material	Stainless Steel
Gasket Material	Silicone Sponge
Rivet Material	Blackened Stainless Steel
Minimum Operating Temperature	-40 °C (-40 °F)
Maximum Operating Temperature	+70 °C (+158 °F)
Approx. Weight	TBC Kg

Standard colour range

Aegis Cases are generally provided in Black, Olive Drab or Portland Stone. Subject to availability other standard colours or bespoke colours are available subject to MOQ.



Testing and Approvals:

MIL-STD-810G, STANAG 4280, STANAG 4340, IP67, ATA 300
Def Stan 81-144, Def Stan 00-035 Part 3, Def Stan 81-041 Part 4.

Dimensional Tolerances +/- 1% of stated dimensions